



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER OF PATENTS AND TRADEMARKS
Washington, D.C. 20231
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/866,311	05/25/2001	David Allan Cook	06007/37458	4324

4743 7590 10/02/2002

MARSHALL, GERSTEIN & BORUN
6300 SEARS TOWER
233 SOUTH WACKER
CHICAGO, IL 60606-6357

[REDACTED] EXAMINER

LOPEZ, FRANK D

[REDACTED] ART UNIT

[REDACTED] PAPER NUMBER

3745

DATE MAILED: 10/02/2002

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary	Application No.	Applicant(s)
	09/866,311	COOK ET AL.
	Examiner	Art Unit
	F. Daniel Lopez	3745

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
- Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) Responsive to communication(s) filed on _____.
- 2a) This action is FINAL. 2b) This action is non-final.
- 3) Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) Claim(s) 1-6 is/are pending in the application.
 - 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) Claim(s) _____ is/are allowed.
- 6) Claim(s) 1-6 is/are rejected.
- 7) Claim(s) _____ is/are objected to.
- 8) Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) The specification is objected to by the Examiner.
- 10) The drawing(s) filed on _____ is/are: a) accepted or b) objected to by the Examiner.

Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
- 11) The proposed drawing correction filed on _____ is: a) approved b) disapproved by the Examiner.

If approved, corrected drawings are required in reply to this Office action.
- 12) The oath or declaration is objected to by the Examiner.

Priority under 35 U.S.C. §§ 119 and 120

- 13) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
 - a) All b) Some * c) None of:
 1. Certified copies of the priority documents have been received.
 2. Certified copies of the priority documents have been received in Application No. _____.
 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.
- 14) Acknowledgment is made of a claim for domestic priority under 35 U.S.C. § 119(e) (to a provisional application).
 - a) The translation of the foreign language provisional application has been received.
- 15) Acknowledgment is made of a claim for domestic priority under 35 U.S.C. §§ 120 and/or 121.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) Paper No(s). _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO-1449) Paper No(s) Z. | 6) <input type="checkbox"/> Other: _____ |

Claim Rejections - 35 USC § 112

Claims 1-6 are rejected under 35 U.S.C. § 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Throughout the claims (e.g. claim 1 line 5) "ram" should be --cylinder—or —piston cylinder device--, since a ram refers to an actuator with one chamber. In claim 1 line 11-12 "the other chamber" has no antecedent basis. In claim 1 line 19 "said first chamber" and line 20 "said second chamber" are wrong, since they refer back to "one chamber" and the "other chamber" of lines 11 and 12, respectively.

In claim 3 line 3 "said ride improvement means" has no antecedent basis.

In claim 6 line 2 "solenoid valves" should be control valves--, to agree with claim 1 line 15. In claim 6 line 2 "check valves" should be —check valve--, to agree with claim 1 line 21.

In claim 4 line 3 "boom" should be —arm--, to agree with claim 1 line 1.

Claims not specifically mentioned are indefinite, since they depend from claim 1.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. § 103 which forms the basis for all obviousness rejections set forth in this Office action:

A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Subject matter developed by another person, which qualifies as prior art only under subsection (f) or (g) of section 102 of this title, shall not preclude patentability under this section where the subject matter and the claimed invention were, at the time the invention was made, owned by the same person or subject to an obligation of assignment to the same person.

Claims 1-4 and 6 are rejected under 35 U.S.C. § 103 as being unpatentable over Bauer in view of Marchi et al and Drake et al. Bauer discloses a wheeled loader comprising an arm (21) pivotally connected at a rear end of a body (12, 13) and

extending forwardly, such that a working implement (27) is in front of the body; a cylinder (25, 26) having first and second chambers (connected to 230, 231, respectively) connected to a manually operated selection valve (80), wherein the arm is raised when the selection valve allows pressurized fluid into the first chamber and accepts fluid under a lower pressure from the second chamber, and wherein the arm is lowered when the selection valve allows pressurized fluid into the second chamber and accepts fluid under a lower pressure from the first chamber; but does not disclose first and second electrically operated solenoid type control valves having a first position where passage of fluid in at least one direction is prohibited and having a second position where passage of fluid therethrough is allowed, with the first control valve connected between the first chamber and an accumulator and the second control valve connected between the second chamber and a low pressure region; wherein a manually operated switch supplies current to the solenoid valves; wherein a switch senses a position of the selection valve to close the second control valve when the arm is lowered and the control valves are open; that there is a check valve connected between the first chamber and the selection valve, preventing flow from the first chamber to the selection valve, with a means for connecting the second chamber to a fluid responsive means to open the check valve; or that at least one of the accumulator, solenoid valves, check valve and connecting pipes are made of metal.

Marchi et al teaches, for a wheeled loader comprising an arm (e.g. 14) pivotally connected to a body (10); a cylinder (18) having first and second chambers (26, 24) connected to a manually operated selection valve (34), wherein the arm is raised when the selection valve allows pressurized fluid into the first chamber and accepts fluid under a lower pressure from the second chamber, and wherein the arm is lowered when the selection valve allows pressurized fluid into the second chamber and accepts fluid under a lower pressure from the first chamber; that there is a check valve (42) mounted directly to the cylinder and connected between the first chamber and the selection valve, preventing flow from the first chamber to the selection valve, with a means (46) for connecting the second chamber to a fluid responsive means to open the check

Art Unit: 3745

valve, for the purpose of preventing a drop of the arm when a fluid passage fails (e.g. column 2 line 42-47).

Since Bauer and Marchi et al are both from the same field of endeavor, the purpose disclosed by Marchi et al would have been recognized in the pertinent art of Bauer. It would have been obvious at the time the invention was made to one having ordinary skill in the art to mount a check valve directly to the cylinder and connect the check valve between the first chamber and the selection valve of Bauer, preventing flow from the first chamber to the selection valve, with a means for connecting the second chamber to a fluid responsive means to open the check valve, as taught by Marchi et al, for the purpose of preventing a drop of the arm when a fluid passage fails.

Drake et al teaches, for a wheeled loader comprising an arm (22) pivotally connected to a body (12); a cylinder (32, 34) having first and second chambers (42, 44) connected to a manually operated selection valve (46), wherein the arm is raised when the selection valve allows pressurized fluid into the first chamber and accepts fluid under a lower pressure from the second chamber, and wherein the arm is lowered when the selection valve allows pressurized fluid into the second chamber and accepts fluid under a lower pressure from the first chamber; that there are first and second electrically operated solenoid type control valves (74, 76) having a first position where passage of fluid in at least one direction is prohibited and having a second position where passage of fluid therethrough is allowed, with the first control valve connected between the first chamber and an accumulator (72) and the second control valve connected between the second chamber and a low pressure region (28); wherein a manually operated switch (84) supplies current to the solenoid valves; and a switch (86) senses a position of the selection valve to close the second control valve when the arm is lowered and the control valves are open, for the purpose of absorbing shocks from the bucket to provide a smoother ride.

Since Bauer and Drake et al are both from the same field of endeavor, the purpose disclosed by Drake et al would have been recognized in the pertinent art of Bauer. It would have been obvious at the time the invention was made to one having ordinary skill in the art to provide first and second electrically operated solenoid type

Art Unit: 3745

control valves (74, 76) having a first position where passage of fluid in at least one direction is prohibited and having a second position where passage of fluid therethrough is allowed, with the first control valve connected between the first chamber and an accumulator of Bauer and the second control valve connected between the second chamber and a low pressure region of Bauer; wherein a manually operated switch supplies current to the solenoid valves; and another switch senses a position of the selection valve to close the second control valve when the arm is lowered and the control valves are open, as taught by Drake et al, for the purpose of absorbing shocks from the bucket to provide a smoother ride.

Official notice is taken that it is well known to make at least one of the accumulator, solenoid valves, check valve and connecting pipes from metal. It would have been obvious at the time the invention was made to one having ordinary skill in the art to make at least one of the accumulator, solenoid valves, check valve and connecting pipes of Bauer from metal, as a matter of engineering expediency.

Claim 5 is rejected under 35 U.S.C. § 103 as being unpatentable over Bauer in view of Marchi et al in view of Drake et al, as applied to claim 1 above, and further in view of Japan 64-66324. The modified Bauer discloses all of the elements of claim 5, but does not disclose that the accumulator and control valves are mounted directly on the cylinder.

Japan 64-66324 teaches, for a wheeled loader comprising an arm pivotally connected to a body (abstract); a cylinder (8) having first and second chambers (8a, 8b) connected to a manually operated selection valve (13), wherein the arm is raised when the selection valve allows pressurized fluid into the first chamber and accepts fluid under a lower pressure from the second chamber, and wherein the arm is lowered when the selection valve allows pressurized fluid into the second chamber and accepts fluid under a lower pressure from the first chamber; with a first electrically operated solenoid type control valve (15) connected between the first chamber and an accumulator (18), and having a first position where passage of fluid in at least one direction is prohibited and having a second position where passage of fluid therethrough is allowed, for

Art Unit: 3745

absorbing shocks from the arm; that the accumulator and control valve are mounted directly on the cylinder.

Since the modified Bauer does not disclose how the accumulator and control valves are mounted, and Japan 64-66324 does; it would have been obvious at the time the invention was made to one having ordinary skill in the art to mount the accumulator and first control valve of the modified Bauer directly on the cylinder, as taught by Japan 64-66324, as a matter of engineering expediency.

Official notice is taken that it is well known to place all valves in a common valve block, for ease of assembly. Since the check valve and the first solenoid valve of the modified Bauer are directly mounted on the cylinder; it would have been obvious at the time the invention was made to one having ordinary skill in the art to place the check valve, and first and second control valves of the modified Bauer in a common block, mounted to the cylinder, for ease of assembly.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Dan Lopez whose telephone number is (703) 308-0008. The examiner can normally be reached on Monday-Thursday from 6:30 AM -4:00 PM. The examiner can also be reached on alternate Fridays.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Ed Look, can be reached on (703) 308-1044. The fax number for this group is (703) 872-9302. Any inquiry of a general nature or relating to the status of this application should be directed to the Group receptionist whose telephone number is (703) 308-0861.



F. Daniel Lopez
Primary Examiner
Art Unit 3745
September 25, 2002